

MATERIAL:

- Segjärn
- Packningar: EPDM
- Bult: Rostfritt A2 stål
- Muttrar: Syrafast A4 stål
- Korrosionsskydd: Epoxy enligt DIN 30722-2


PÅ FÖRFRÅGAN

Packningar av NBR




IBECO RDS gjutna repmuffar, 2-delad

Art. nr.	RSK nr.	DN	Bygglängd mm	Spännvidd mm	Vikt kg
0605041A2	103 08 79	40	200	48- 56	5,5
0605040A2	103 08 80	40	200	54- 61	5,5
0605050A2	103 08 82	50	210	60- 68	5,9
0605070A2	103 08 83	70	210	76- 87	8,2
0605080A2	103 08 84	80	210	89- 98	8,4
0605081A2	103 08 85	80	210	95- 108	8,9
0605100A2	103 08 86	100	240	108- 118	11,0
0605101A2	103 08 87	100	240	116- 128	12,0
0605125A2	103 08 88	125	240	133- 144	12,5
0605125a2	109 91 28	125	300	142- 153	
0605150A2	103 08 89	150	300	159- 172	22,0
0605151A2	103 08 90	150	300	168- 184	24,0
0605175A2	103 08 91	175	300	193- 205	26,0
0605200A2	103 08 92	200	400	214- 225	33,5
0605250A2	103 08 93	250	450	267- 274	61,5
0605300A2	103 08 94	300	500	315- 326	79,5



IBECO RDS gjutna repmuffar, 3-delad

Art. nr.	RSK nr.	DN	Bygglängd mm	Spännvidd mm	Vikt kg
0601080A2	109 90 97	80	150	89- 108	7,9
0601100A2	109 90 98	100	160	108- 128	8,9
0601125A2	109 90 99	125	210	133- 155	11,5
0601150A2	109 91 00	150	210	159- 184	15,5
0601200A2	109 91 01	200	260	216- 238	21,5



IBECO RDS gjutna repmuffar, 3-delad med gängat uttag

Art. nr.	RSK nr.	DN	Avstick	Bygglängd mm	Spännvidd mm	Vikt kg
06.06.004.080	109 91 02	80	inv. G50	150	89- 108	7,9
06.06.004.100	109 91 03	100	inv. G50	160	108- 128	8,9
06.06.004.125	109 91 04	125	inv. G50	210	133- 155	11,5
06.06.004.150	109 91 05	150	inv. G50	210	159- 184	15,5
06.06.004.200	109 91 06	200	inv. G50	260	216- 238	21,5

GODKÄNNANDEN:
KTW W270


DVGW AT2512



SS-EN 681-1